

Dricon Sand and Aggregate Products Safety Data Sheet

1. Identification of Substance & Company

Product		
Product name	Dricon Sand and Aggregate Products	
Other names	Sand	Pea Metals
	No 1 Sand	Pea metal A
	No 17 Sand	Pea metal B
	10 Mesh Sand	Pea metal C
	Castle Sand	
	Bowling Sand	
	Dune Sand	
	East coast sand	Blended products
	Filter Sand	Builders mix
	Helensville Sand	Builders sand
	Tennis Sand	Plaster sand
	Traction Sand	Pavejoint sand
	TUS Sand	Casting sand
	Cedar Chip	
	Ashwood Chip	
	Charcoal Chip	
Product code	NA	
HSNO approval	HSR002545	
Approval description	Construction Products (Toxic [6.7A]) Group Standard 2017	
UN number	Not allocated	
Proper Shipping Name	NA	
Packaging group	NA	
Hazchem code	1T (recommended)	
Uses	Bowling greens, concretes, morta	ars, plasters, grouts, paints, water filtration,
	pave jointing, infill, fluid beds, arti	ficial sports turf, locomotive traction,
	drainage, roofing chip	• •
Company Details		
Company	Dricon, Firth Industries	
Address	100 Bollard Rd,	
	Tuakau	
	Auckland	

Telephone Website

Emergency Telephone Number: 0800-764 766

0800 374 266

www.dricon.co.nz

2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002545, Construction Products (Toxic [6.7A]) Group Standard 2017), and is classified as follows:

Classes	Hazard Statement
6.7A	H350 - May cause cancer if inhaled (contains crystalline silica)
6.9A	H372 - Causes damage to organs through prolonged or repeated exposure if inhaled. (may cause silicosis and effects to the lungs)

SYMBOLS





FOR 24 HOUR POISON ADVICE CALL 0800 POISON (0800 764 766)

Other Classifications

There are no other classifications that are known to apply.

Precautionary Statements

P103 - Read label before use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

- P281 Use personal protective equipment as required.
- P308+P313 IF exposed or concerned: Get medical advice/ attention.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Crystalline silica	14808-60-7	<50%
Naturally occurring metal oxides	Not known	<5%
Non hazardous silicates and oxides	Not known	balance

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

You should call the National Poisons Centre if you feel that you may have been harmed by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

If medical advice is needed, have this SDS, product container or label at hand. If exposed or concerned: Get medical advice/ attention.

Recommended first aid
Ready access to running water is recommended. Accessible evenash is recommended.

facilities	heady access to running water is recommended. Accessible eyewash is recommended
Exposure	
Swallowed	Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor if experiencing symptoms.
Eye contact	If product gets in eyes, wash material from them with running water for several minutes. If symptoms persist, seek medical advice.
Skin contact	This product is non-irritating to skin. No further measures should be required.
Inhaled	If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor.

Advice to Doctor

Treat symptomatically. See Section 11 for information on potential long term health effects from exposure to very fine crystalline silica dust.

5. Firefighting Measures

Fire and explosion hazards: Suitable extinguishing substances:	There are no specific risks for fire/explosion for this chemical. It is non-combustible. Not applicable.
Unsuitable extinguishing substances:	Unknown.
Products of combustion:	Product does not burn. Dust may form irritating atmosphere. Product will react exothermically with water. Contaminated water wil be strongly alkaline. Product may decompose in a fire and produce toxic or corrosive fumes.
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	1T (recommended)



6. Accidental Release Measures

Containment	Emergency plans to manage any potential spills must be in place. Prevent spillage from spreading or entering soil, waterways or drains.
Emergency procedures	In the event of large spillage alert the fire brigade to location and give brief description of hazard. Wear protective equipment to prevent respiratory exposure. Clear area of any unprotected personnel. Sweep up the solid. Avoid creating dust. If appropriate, use a gentle water spray to wet material to minimise dust generation.
Clean-up method Disposal	Collect and seal in properly labelled containers or drums for disposal or recycling. Sweep up and collect recoverable material into labelled containers for recycling or salvage. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent the inhalation of dusts. Work up wind or increase ventilation.
	7. Storage & Handling
Storage Handling	Stable under normal use and storage conditions. Keep exposure to dusts to a minimum, and minimise the quantities kept in work areas.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

0		•	
NZ Workplace	Ingredient	WES-TWA	WES-STEL
Exposure Stds	Crystalline Silica (all forms)	0.1mg/m ³ (as respirable dust)	no data

* These workplace exposure standards are also Prescribed Exposure Standards (PES) under the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016.

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment Eyes

Skin

Respiratory

Protective eyewear is not normally necessary when using this product. However, it always prudent to use protective eyewear if dust is likely.

Minimise dust generation and accummulation. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of dust.

Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Wash contaminated clothing before re-use.

To prevent irritation a well fitted dust mask should be used (this is not recommended when exposure is close to the WES). A fine particulate half or full face respirator with an effective seal is recommended when airborne concentrations approach the WES (section 8). If sanding, grinding, crushing or cutting concrete, it is possible that the silica dust WES (0.02 mg/m³) will be exceeded hence a respirator will be required. If exposure to the concentrated aqueous solution, dust and mist is likely, a full face respirator with a particulate filter is recommended.

WES Additional Information

Air monitoring to measure the overall amount of silica dust created at various positions on the worksite and the maximum level of worker exposure (given the use of dust control methods, respirators and other measures) should be carried out on a regular bases or when new work methods or equipment is introduced. Air monitoring can be carried out by occupational hygienists or other trained personnel.



Dricon Sand and Aggregate Products Safety Data Sheet

9. Physical & Chemical Properties

Appearance	fine sand		
Appearance Odour	no odour		
рН	no data		
Vapour pressure	no data		
Viscosity	no data		
Boiling point	no data		
Volatile materials	no data		
Freezing / melting point	no data		
Solubility	no data		
Specific gravity / density	no data		
Flash point	no data		
Danger of explosion	no data		
Auto-ignition temperature	no data		
Upper & lower flammable limits	no data		
Corrosiveness	non corrosive		
	10. Stability & Reactivity		
Stability	Stable		
Conditions to be avoided			
Conditions to be avoided	Containers should be kept closed in order to avoid contamination. Avoid the creation of		
	dust.		
Incompatible groups	None known		
Hazardous decomposition	None known		
products			
Hazardous reactions	None known		
	11. Toxicological Information		

Summary

IF SWALLOWED: No adverse effects anticipated under normal use conditions.

IF IN EYES: Fine dust may cause irritation when in direct contact.

IF ON SKIN: No adverse effects anticipated under normal use conditions.

IF INHALED: Short term (acute) silicosis can occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

CHRONIC EFFECTS: The dust does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of concrete). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer. In addition to silicosis there is some evidence that exposure to respirable crystalline silica may be linked to scleroderma and an increased risk of kidney disease.

Supporti	ng Data	
Acute	Oral	Not considered acutely toxic if swallowed.
	Dermal	Not considered acutely toxic by dermal contact.
	Inhaled	The substance is not considered acutely toxic if inhaled, however there may be irritation of the respiratory tract if dust is inhaled. Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.
	Eye	The mixture is not considered to be an eye irritant. Dust may be an eye irritant (mechanical irritation).
	Skin	The mixture is not considered to be a skin irritant.

*	DRI	CON®	

Chronic	Sensitisation Mutagenicity Carcinogenicity	No ingredient present at concentrations > 0.1% is considered a sensitizer. No ingredient present at concentrations > 0.1% is considered a mutagen. The dust resulting from this product does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). Crystalline Silica triggers 6.7A classification (confirmed carcinogen). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of quartz containing substrates). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer.
	Reproductive / Developmental Systemic	No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation. The dust of this product is considered to be a target organ toxicant, because of the presence of crystalline silica at greater than 1%. Crystalline silica triggers 6.9A classification if it is in the form of a fine respirable dust in an occupational (chronic exposure) setting. This is due to the development of silicosis which can occur following exposure to extremely high levels of fine silica dust. Silicosis is a type of pneumoconiosis – a disease of the lung that causes inflammation, scar tissue, lesions and fibrosis in the lung (alveolar). Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). Silicosis can occur following prolonged exposure (e.g., 10 years) to relatively high levels of fine crystalline silica dust.
	Aggravation of existing conditions	Persons with existing lung conditions may be at a higher risk of further adverse health effects (as above). Smokers have an increased risk of lung cancer and silicosis.
		12. Ecological Data
Summary This mixtu	, Ire is not considered hari	mful or ecotoxic.

This mixture is not considered h	armful or ecotoxic.
Supporting Data	
Aquatic	No evidence of aquatic toxicity for any of the ingredients present >1%.
Bioaccumulation	No evidence of bioaccumulation
Degradability	Not applicable.
Soil	No evidence of soil toxicity.
Terrestrial vertebrate	Not considered to be toxic towards terrestrial vertebrates
Terrestrial invertebrate	No evidence of toxicity towards terrestrial invertebrates.
Biocidal	no data
	13. Disposal Considerations
Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

14. Transport Information					
Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007					
This mixture is not considered a dangerous good for transport on land.					
UN number:	NA	Proper shipping name:	NA		
Class(es)	NA	Packing group:	NA		
Precautions:	NA	Hazchem code:	1T (recommended)		

Dricon Sand and Aggregate Products Safety Data Sheet

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545: Construction Products (Toxic [6.7A]) Group Standard 2017.

Specific Controls

Key workplace requirements are:	
SDS	To be available within 10 minutes in workplaces storing any quantity.
Inventory	An inventory of all hazardous substances must be prepared and maintained.
Packaging	All hazardous substances should be appropriately packaged including substances that have been decanted, transferred or manufactured for own use or have been supplied
Labelling	Must comply with the Hazardous Substances (Labelling) Notice 2017.
Emergency plan	Required if > 1000kg is stored.
Certified handler	Not required.
Tracking	Not required.
Bunding and secondary containment	Required if > 1000kg is stored.
Signage	Required if > 10000kg is stored.
Location compliance certificate	Not required.
Flammable zone	Not required.
Fire extinguisher	Not required.
Note: The above workplace requirement	ate apply if only this particular substance is present. The complete set of controls for

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

	16. Other Information
Abbreviations	
Approval Code	Approval Construction Products (Toxic [6.7A]) Group Standard 2017, Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Ceiling	Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC ₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (New Zealand)
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL	Lower Explosive Limit
	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC ₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
PES	Prescribed Exposure Standard means a WES or a biological exposure standard that is prescribed in a regulation, a safe work instrument or an approval under HSNO (including group standards).
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UEL	Upper Explosive Limit
UN Number	United Nations Number
WES	Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.
Page 6 of 7	

FOR 24 HOUR POISON ADVICE CALL 0800 POISON (0800 764 766)



References	
Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).
Controls	EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances) Regulations 2017, www.legislation.govt.nz
WES	The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz.
Other References:	EU ECHA, ingredients SDS's, ChemIDplus
Review	
Date June 2018	Reason for Review NA – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications, are based on our experience, EPA Guidelines and international classifications. A compliance record is available on request. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: (09) 940 30 80.

